LUBEonline
online lubrication services

Lubebeta TG: Tackiness Gear Oil

ผลิตภัณฑ์

Lubebeta TG น้ำมันเกียร์ซุปเปอร์เรดผลิตจากน้ำมันพื้นฐานพาราฟินิคที่มีคุณภาพสูง ผสมด้วยหัวเชื้อที่ทนต่อแรงกด รวมทั้งหัวเชื้อที่ลดการเกิดฟองและต้านทานการรวมตัวกับน้ำ Lubebeta TG ผลิตได้ตามมาตรฐานและเหนือกว่ามาตรฐาน API GL-5 และผ่านมาตรฐานทางทหาร MIL-L 2105C Lubebeta TG แนะนำให้ใช้งานกับเกียร์ที่รับภาระหนักในอุตสาหกรรมทั่วไป รวมทั้งเกียร์เฟืองท้ายในรถบรรทุกและแทรกเตอร์ที่ใช้งานหนัก

การใช้งาน

Lubebeta TG มีส่วนผสมของหัวเชื้อ Tackiness Agent ช่วยยึดเกาะกับเฟืองเกียร์
- สามารถทนต่อแรงกดดันได้อย่างดีเลิศ
- มีฟิลม์ที่เหนียวและทนทานต่อแรงกดสูง
- ลดการเกิดฟอง, ลดการสึกหรอ, ยืดอายุของซีล
- ความหนืดคงที่แม้อุณหภูมิจะเปลี่ยนไป

คุณประโยชน์

Lubebeta TG เหมาะสำหรับเฟืองเกียร์ปิดทุกชนิด เช่น Spur, Worm, Hypoid, Bevel และเฟืองท้ายทุกชนิด Lubebeta TG ไม่แนะนำให้ใช้กับระบบเกียร์อัตโนมัติ, เกียร์ทอล์ค, ระบบเกียร์ในรถยนต์บางรุ่น ใน Crank Case ซึ่งผู้ผลิตแนะนำให้ใช้ Pure Mineral Gear Lubricant อายุการเปลี่ยนถ่ายปลี่ยนน้ำมันทุก 80,000 กม. หรือทุกๆ 6,000 ชั่วโมง

SAE Grade	90	140
Viscosity, cSt @ 40 °C	220	460
cSt @ 100°C	17.5	30.5
Viscosity Index	84	96
Flash Point, °C	205	215
Density @ 15 °C	0.89	0.90
Service Hours	---------6,000 hours -------	
Additives	Dispersant adhesive, Anti-Oxidant, EP, Rust Inhibitor	

The technical informations in this data sheet represents our present knowledge. It does not form part of any sales contract as guaranteed properties of the delivered material. Since the condition of use are beyond our control