

LUBEonline

online lubrication services

Lubealfa SFL: Semi-Fluid LT Grease

Description

Lubealfa SFL is a superior semi-fluid lubricant that specifically developed for lubrication of Pin Bushing including a similar Industrial Bushing & conveyors which are necessary for this special type of lubricant that can be penetrated into the tiny part of machine or centralize lubrication.

Typical Uses

- Lubealfa SFL is recommended for centralized lubrication, Pin-Bushing Trac-Roller of Tractor and also on chain in dusty condition.
- Lubealfa SFL is recommended for using in motor gear reduction in which the manufacturer recommend grease NGLI No. 0 to protect oil leakage.

Advantages

- Contains polar element compounds which cause tenacious to metal forming and strong protective film.
- Positively dose not drip even when equipment is idle.
- Flowing freely through tiny grease passages in Trac-Roller or small pin are as in conveyor application providing full and proper lubrication at all times.

NLGI Grade	0	00	000
Work Penetration @ 25 ° C	355-385	410-440	445-475
Thickener	-----LT-----		
Dropping Point, °F, Min	380	360	360
Flash Point, °F, Min	342	324	324
Consistency	-----Semi-Fluid-----		
Operating temperature, ° F	----- 0-380 -----		
Color	Yellow		
Additives	EP, Anti-wear, Anti- Oxidation		